



Please see reverse for a full guide to choosing your BRITEK Actuator Button(s)

FIW

The BRITEK In Wall Cistern delivers a robust, vandal-resistant flushing solution tailored for modern commercial and accessible washroom environments.

Features and Benefits

- **Ultra Slim 80mm Tank** – Ideal for compact installations, including between 410mm studs within an 85mm cavity wall.
- **Accessible Button Options** – Compliant with AS1428 standards
- **Flexible Installation** – Mountable in-wall, in-ceiling, or in-duct with options for remote access and serviceability.
- **WELS & WaterMark Certified**– Assures performance, efficiency, and adherence to Australian plumbing standards.

Sample Spec

*BRITEK InWall Dual Flush Cistern. Remote stainless steel actuator plate. Remote stainless steel actuator face plate and buttons to be **low profile/raised/security/institutional** type. Cistern set to **X/X** litre flush capacity. WaterMark and WELS certified - Product Code FIW-XXX*

*RED TEXT may denote a **variable** where one option only is to be selected, a **nominal dimension** that needs to be specified, or an **optional feature** that can be removed if not required. Please refer to the back of this page for additional specification details and options.

HOW TO SPECIFY: In Wall Dual Flush Cistern with Pneumatic Actuators

Sample Specification Code

Specification Key

A **B**
FIW - S63

= In Wall Dual Flush Cistern
with Pneumatic Actuators


A = Product Code
B = Flush Volume

A GUIDE TO:

BRITEX FIW Actuator Options

PLEASE READ: Actuator Buttons cannot be installed directly in front of the Cisterns Service Access Point. A Panel (PAPL) is provided to cover the opening and allow access.

Contact BRITEX for options of button assemblies to go directly behind the cistern.



Standard Actuator Plates

*Please see FIW Install Guide for more info

Britex Actuator Button Options

Britex Plate Options	Standard Buttons	Accessible Buttons 	Single Flush
	Low Profile Buttons Dual Flush	Raised Access Buttons Dual Flush	
	 Standard Plates Pneumatic Actuator with In Wall Cistern Standard Plate 200x95mm	 FIW-S63: 3/6L FIW-S453: 3/4.5L	 FIW-SP18: 1.8L (suitable for urinals) FIW-SP45: 4.5L (suitable for slophopper)
	 Mechanical Actuator Direct Access Plate with In Wall Cistern Standard Plate 246x164mm SPARE PARTS: DIRECT ACCESS PLATES AVAILABLE PAPL: 255x175mm Direct Access Plate Only PAPL-2: 255x175mm Direct Access Plate with button holes cut out to suit BRITEX Low Profile or Raised Buttons - for retrofitting.	 FIW-M453: 3/4.5L	 not suitable
	 Security Plates Pneumatic Actuator with In Wall Cistern (remotely located) Security plate includes penitentiary fixings and security enclosure for direct installation into stud wall for added vandal resistance	 FIW-SEC63: 3/6L FIW-SEC453: 3/4.5L	 FIW-SEC-P1: 4.5L Front Fixed FIW-NSWC: 4.5L Rear Fixed

NOTE: To fully engage flush volume, push and hold button for 2 seconds.

Add ons:

- Flow restrictor - for high level mounted cisterns
- Direct Access Plate - PAPL

VISIT BRITEX.COM.AU TO DOWNLOAD BIM FILES, CAD DRAWINGS AND THE MOST CURRENT PRODUCT LITERATURE.

Last Revised 29 Jul 2025 | Rev 2